


ZW-33Z

Cross-beam LED Digital Control Box



- Medium-sized sleek design dark grey premium finish;
- High sensitivity 33 zones (11vertical 3 lateral);
- Detect ferrous & non-ferrous metal objects;
- Pre-set 72 scene for easy operation;

• Comply with EMC electromagnetic radiation standards and adopt weak magnetic field technology, harmless to pacemaker wearers, pregnant women, floppy disks, film and video tapes

Conform to Electricity EN60950 Safety Standard Conform to Radiation EN50081-1 Standard Conform to Anti-interference EN50082-1 Standard










ZW-33Z

Product Specification

Overall Exterior Size	2191*875*445mm
Passageway Interior Size	2007*720*445mm
Operating Voltage	AC100V ~ 240V 50 / 60Hz
Power	12W
Operating Temperatures	-20°C ~ 65°C
	Width 100cm* Length
Installation Environment	200cm (minimum range
	without metal)



Function Configuration


Detection Zones	11-22-33 Zones	
Pass Count	0-99999	
Alarm Count	0-99999	
Metal Detection Accuracy Range	One-dollar coin	
User Interface	Dual sets of bright red and green digital tube display + integrated four-button panel operation mode	
Password Protection Function	5-digit password protection	
Metal Position Indicator	Intelligent zoning indication	
Operating Frequency	0-99	
Security Level	0-99	
Sensitivity Level	0-400	
Alarm Volume	0-99	
Alarm Tone	0-99	
Alarm Time	0-99	
Scene Setting	72 preset scenes	
Infrared Setting	0-Both groups OFF	
	1-Front group ON	
	2-Rear group ON	
	3-Both groups ON	
Left and right LED Bars	Interchangeable	
LED Alarm Bars	Front 2 groups	
Simultaneous detection and alarm	2 Detection zones simultaneously alarm	
in multiple zones		




ZW-33Z


Optional Functions: The above zones can be equipped with the		
following functions		
Turnstile Connection		
D Networking Interfaces for Multiple Units	┠╼╼┦	
Back up Battery : 4/8/16 Hours	With optional functions	No optional functions
Front and Rear Panel Alarm LED Lights		
Secondary Development Port/Upgrade Port		

Interface Display



Anti-interference Reference Standard









Keep ≥80cm from the X-Ray machine

Keep ≥50cm between two units


Keep \geq 10cm from the wall

Note: The above distances are for reference only, and the actual distances shall be subject to the performance accuracy of on-site debugging; the higher the sensitivity, the greater the distance interval, and the lower the sensitivity, the smaller the distance interval.






Test kits



Detection Zone



Package

Packaging:	Carton box
Package Size:	L2285xW665xH215mm
Volume:	0.33m³
Net weight:	35kgs
Gross weight:	42kgs



